

DIGITAL TV

DECKtron

Vivid Picture, Vivid in Your memory!

Digital TV from Decktron

2005



design

B

DIGITAL LCD TV

Presenting the most impressive design.

DL37-B

Luminance : 500cd/m²

Contrast Ratio : 600 : 1

Aspect Ratio : 16:9

Resolutions : 1,366 * RGB * 768

Viewing Angle : L/R 176, U/D 176

Double Window PIP, Small PIP

Nicam stereo(Europe)/MTS Stereo & SAP

Progressive Scan 480i/p, 576i/p, 720p/1080i





20" 26" 32" 37" (42")

DL20-B

Luminance : 450cd/m²
 Contrast Ratio : 350 : 1
 Aspect Ratio : 4:3
 Resolutions : 640 * RGB * 480
 Viewing Angle : L/R 176, U/D 176
 Small PIP
 Nicam stereo(Europe)/MTS Stereo & SAP
 Progressive Scan 480i/p,576i/p

DL26-B

Luminance : 450cd/m²
 Contrast Ratio : 500 : 1
 Aspect Ratio : 16:9
 Resolutions : 1,280 * RGB * 768
 Viewing Angle : L/R 176, U/D 176
 Double Window PIP, Small PIP
 Nicam stereo(Europe)/MTS Stereo & SAP
 Progressive Scan 480i/p,576i/p,720p/1080i

DL32-B

Luminance : 500cd/m²
 Contrast Ratio : 600 : 1
 Aspect Ratio : 16:9
 Resolutions : 1,366 * RGB * 768
 Viewing Angle : L/R 176, U/D 176
 Double Window PIP, Small PIP
 Nicam stereo(Europe)/MTS Stereo & SAP
 Progressive Scan 480i/p,576i/p,720p/1080i



design

G

DIGITAL LCD TV

Reaching the highest level of picture quality



DL32-G

Luminance : 500cd/m²

Contrast Ratio : 600 : 1

Aspect Ratio : 16:9

Resolutions : 1,366 * RGB * 768

Viewing Angle : L/R 176, U/D 176

Double Window PIP, Small PIP

Nicam stereo(Europe)/MTS Stereo & SAP

Progressive Scan 480i/p, 576i/p, 720p/1080i



26" 32" 37" 42"

DL26-G

Luminance : 500cd/m²
 Contrast Ratio : 600 : 1
 Aspect Ratio : 16:9
 Resolutions : 1,366 * RGB * 768
 Viewing Angle : L/R 176, U/D 176
 Double Window PIP, Small PIP
 Nicam stereo (Europe) / MTS Stereo & SAP
 Progressive Scan 480i/p, 576i/p, 720p/1080i



DL37-G

Luminance : 500cd/m²
 Contrast Ratio : 600 : 1
 Aspect Ratio : 16:9
 Resolutions : 1,366 * RGB * 768
 Viewing Angle : L/R 176, U/D 176
 Double Window PIP, Small PIP
 Nicam stereo (Europe) / MTS Stereo & SAP
 Progressive Scan 480i/p, 576i/p, 720p/1080i



DL42-G

Luminance : 500cd/m²
 Contrast Ratio : 500 : 1
 Aspect Ratio : 16:9
 Resolutions : 1,366 * RGB * 768
 Viewing Angle : L/R 176, U/D 176
 Double Window PIP, Small PIP
 Nicam stereo (Europe) / MTS Stereo & SAP
 Progressive Scan 480i/p, 576i/p, 720p/1080i



design

C

DIGITAL LCD TV

Mirror your unique lifestyle with LCD.



aluminium

DL37-C

Luminance : 500cd/m²

Contrast Ratio : 600 : 1

Aspect Ratio : 16:9

Resolutions : 1,366 * RGB * 768

Viewing Angle : L/R 176, U/D 176

Double Window PIP, Small PIP

Nicam stereo(Europe)/MTS Stereo & SAP

Progressive Scan 480i/p, 576i/p, 720p/1080i



32" 37" 42" 47" (40")

DL32-C

Luminance : 500cd/m²
 Contrast Ratio : 600 : 1
 Aspect Ratio : 16:9
 Resolutions : 1,366 * RGB * 768
 Viewing Angle : L/R 176, U/D 176
 Double Window PIP, Small PIP
 Nicam stereo(Europe)/MTS Stereo & SAP
 Progressive Scan 480i/p, 576i/p, 720p/1080i

DL42-C

Luminance : 500cd/m²
 Contrast Ratio : 500 : 1
 Aspect Ratio : 16:9
 Resolutions : 1,366 * RGB * 768
 Viewing Angle : L/R 176, U/D 176
 Double Window PIP, Small PIP
 Nicam stereo(Europe)/MTS Stereo & SAP
 Progressive Scan 480i/p, 576i/p, 720p/1080i

*Detachable Speaker



design

K

DIGITAL LCD TV

Presenting the most impressive design.

DL37-K

Luminance : 500cd/m²

Contrast Ratio : 600 : 1

Aspect Ratio : 16:9

Resolutions : 1,366 * RGB * 768

Viewing Angle : L/R 176, U/D 176

Double Window PIP, Small PIP

Nicam stereo(Europe)/MTS Stereo & SAP

Progressive Scan 480i/p, 576i/p, 720p/1080i



• aluminium



DECKTRON Television
LCD TV

37" (32"42")

DL32-K

Luminance : 500cd/m²
 Contrast Ratio : 600 : 1
 Aspect Ratio : 16:9
 Resolutions : 1,366 * RGB * 768
 Viewing Angle : L/R 176, U/D 176
 Double Window PIP, Small PIP
 Nicam stereo(Europe)/MTS Stereo & SAP
 Progressive Scan 480i/p, 576i/p, 720p/1080i

DL42-K

Luminance : 500cd/m²
 Contrast Ratio : 500 : 1
 Aspect Ratio : 16:9
 Resolutions : 1,366 * RGB * 768
 Viewing Angle : L/R 176, U/D 176
 Double Window PIP, Small PIP
 Nicam stereo(Europe)/MTS Stereo & SAP
 Progressive Scan 480i/p, 576i/p, 720p/1080i



design

M

DIGITAL LCD TV

The impact of style simplicity.



DL37-M

Luminance : 500cd/m²

Contrast Ratio : 600 : 1

Aspect Ratio : 16:9

Resolutions : 1,366 * RGB * 768

Viewing Angle : L/R 176, U/D 176

Double Window PIP, Small PIP

Nicam stereo(Europe)/MTS Stereo & SAP

Progressive Scan 480i/p, 576i/p, 720p/1080i



26" 32" 37" 42"

DL26-M

Luminance : 500cd/m²
 Contrast Ratio : 600 : 1
 Aspect Ratio : 16:9
 Resolutions : 1,366 * RGB * 768
 Viewing Angle : L/R 176, U/D 176
 Double Window PIP, Small PIP
 Nicam stereo (Europe)/MTS Stereo & SAP
 Progressive Scan 480i/p, 576i/p, 720p/1080i

DL32-M

Luminance : 500cd/m²
 Contrast Ratio : 600 : 1
 Aspect Ratio : 16:9
 Resolutions : 1,366 * RGB * 768
 Viewing Angle : L/R 176, U/D 176
 Double Window PIP, Small PIP
 Nicam stereo (Europe)/MTS Stereo & SAP
 Progressive Scan 480i/p, 576i/p, 720p/1080i

DL42-M

Luminance : 500cd/m²
 Contrast Ratio : 500 : 1
 Aspect Ratio : 16:9
 Resolutions : 1,366 * RGB * 768
 Viewing Angle : L/R 176, U/D 176
 Double Window PIP, Small PIP
 Nicam stereo (Europe)/MTS Stereo & SAP
 Progressive Scan 480i/p, 576i/p, 720p/1080i



*Card Reders : SD, SM, MMC, MS/MS Pro



Specifications-LCD...



Section	Contents	DL20-B20P	DL20-B60P	DL26-G10P	DL26-G22P	DL26-G70P	
Display	Outline Dimension	432(H) mm x 331.5(V) mm	432(H) mm x 331.5(V) mm	626.0(H) mm x 373.0(V) mm	626.0(H) mm x 373.0(V) mm	626.0(H) mm x 373.0(V) mm	
	Active area	408(H) mm x 306(V) mm	408(H) mm x 306(V) mm	566.4(H) mm x 339.8(V) mm	566.4(H) mm x 339.8(V) mm	566.4(H) mm x 339.8(V) mm	
	Aspect Ratio	4 : 3	4 : 3	16 : 9	16 : 9	16 : 9	
	Pixel Pitch	0.2125mm x 0.6375mm x RGB	0.2125mm x 0.6375mm x RGB	147.5mm x 421.5mm x RGB	147.5mm x 421.5mm x RGB	147.5mm x 421.5mm x RGB	
	Resolutions	640 x RGB x 480	640 x RGB x 480	1,366 x RGB x 768	1,366 x RGB x 768	1,366 x RGB x 768	
	Viewing Angle	L/R 176, U/D 176	L/R 176, U/D 176	L/R 176, U/D 176	L/R 176, U/D 176	L/R 176, U/D 176	
	Colors	16.7M	16.7M	16.7M	16.7M	16.7M	
	Luminance	450 cd/m ²	450 cd/m ²	500 cd/m ²	500 cd/m ²	500 cd/m ²	
	Contrast Ratio	350 : 1	350 : 1	600 : 1	600 : 1	600 : 1	
Response Time	25ms	25ms	16 ms	16 ms	16 ms		
System	Tuning	PAL-B/G ,D/K, I SECAM-B/G,D/K,L/L' NTSC AV 3.58/4.43	PAL-B/G ,D/K, I SECAM-B/G,D/K,L/L' NTSC AV 3.58/4.43	PAL-B/G ,D/K, I SECAM-B/G,D/K,L/L' NTSC AV 3.58/4.43	PAL-B/G ,D/K, I SECAM-B/G,D/K,L/L' NTSC AV 3.58/4.43	PAL-B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC AV 3.58/4.43	
	Audio	A2 STEREO NICAM STEREO MTS/SAP(NTSC Area)	A2 STEREO NICAM STEREO MTS/SAP(NTSC Area)	A2 STEREO NICAM STEREO MTS/SAP(NTSC Area)	A2 STEREO NICAM STEREO MTS/SAP(NTSC Area)	A2 STEREO NICAM STEREO MTS/SAP(NTSC Area)	
	Speaker	Side 2 Speaker(Built-in)	Side 2 Speaker(Built-in)	Side 2 Speaker(Built-in)	Side 2 Speaker(Built-in)	Side 2 Speaker(Built-in)	
	Teletext	10 pages	10 pages	200 Page	252 pages	1000 pages	
	V-Chip/CCD	O (US)	O (US)	O (US)	O (US)	O (US)	
	Output	Audio Multi Language OSD Picture	10W(5W x 2W)max ENG/DEUT/FRA/ITA/ESP 4:3	6W(3W x 2W)max ENG/DEUT/FRA/ITA/ESP/PORT 4:3	20W(10W + 10W) / RMS ENG/DEUT/FRA/ITA/ESP Auto wide/Wide/Panorama/Zoom/4:3/14:9	10W(5W x 2W)max ENG/DEUT/FRA/ITA/ESP 16:9 / 4:3	20W(10W + 10W) / RMS ENG/DEUT/FRA/ITA/ESP 16:9;4:3,Zoom,Panorama
	Function	Function	Sleep Timer Picture Tone(Normal/Warm/Cool) Picture (User/Standard/ Movie/Vivid) Sound (User/Standard /Music/Movie/News) Auto Power Off PIP(Only PC Mode) Size/Position Last Source Memory	Sleep Timer Picture Tone(Normal/Warm/Neutral/Cool) Picture (User/Standard/Dynamic/Mild) Sound (User/Standard /Music/Movie/Speech) Sound Tone(Balance,EQ,Surround) On,Off Timer	- Surround Sleep timer On/Off Timer PSM(Custom/Dynamic/Standard/Movie/Mild) SSM(Custom/Standard/Music/Movie/Speech) Movie/User/Surround Auto Power On/Off PIP / DW (Double Window) Still/Move/Swap	3D NR Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher Picture Tone(Normal/Warm/Cool) Picture (User/Standard/ Movie/Vivid) Sound (User/Standard /Music/Movie/News) Sleep Timer/PIP(PC/DVD Mode)	4H Comb Filter Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher APC(Standard/Soft/Custom/Strong) ASC(Standard/Music/Movie/Speech /User/Surround) Auto Power On,Off/Sleep Timer/On,Off Timer PIP/POP/DW
In/Out Terminal	AV input	S-Video PAL : Scart/NTSC : RCA (Option) Component(YPbPr : HDTV Ready)	S-Video PAL : Scart/NTSC : RCA (Option) Component(YPbPr : 480i,576i)	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack	
	PC Video input	RGB In (D-Sub 15-pin)	-	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	
	PC Audio Input	Ear Phone Jack	-	Ear Phone Jack	Ear Phone Jack	Audio L/R RCA Jack	
	DVI Input	-	-	DVI (With HDCP)	DVI (with HDCP)	-	
	RS-232	-	-	Up-Grade	-	O (UP-Grade)	
	HDMI	-	-	-	-	O	
	Speaker	Bulti in Speaker	Bulti in Speaker	Bulti in Speaker	Bulti in Speaker	Bulti in Speaker	
	Head Phone Output	Head Phone Jack	Head Phone Jack	Head Phone Jack	Head Phone Jack	Head Phone Jack	
	Antenna In	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	
	Power	Input Voltage consumption	DC12V Adaptor 60W	DC15V Adaptor 65W	100~240V(50/60Hz) Approx.120W	100~240V(50/60Hz) Approx.120W	100~240V(50/60Hz) Approx.120W
Mechanical Size	Size (W x D x H) mm	584 X 214 X 436(With Stand) 584 x 71 X 392(w/o stand)	584 X 214 X 436(With Stand) 584 x 71 X 392(w/o stand)	814 X 230 x 486(With Stand) 814 x 105.5 X 433.8 (w/o stand)	814 X 230 x 486(With Stand) 814 x 105.5 X 433.8 (w/o stand)	814 X 230 x 486(With Stand) 814 x 105.5 X 433.8 (w/o stand)	
	Weight (N.Weight/ G.Weight)	9.6kg/ 12kg	9.6kg/ 12kg	17kg/20.7kg	17kg/20.7kg	17kg/20.7kg	
Container	20 Feet	264/160(W/O Pallets/With Pallets)	264/160(W/O Pallets/With Pallets)	144/120(W/O Pallets/With Pallets)	144/120(W/O Pallets/With Pallets)	144/120(W/O Pallets/With Pallets)	
	40 Feet	544/352(W/O Pallets/With Pallets)	544/352(W/O Pallets/With Pallets)	312/264(W/O Pallets/With Pallets)	312/264(W/O Pallets/With Pallets)	312/264(W/O Pallets/With Pallets)	
	40 Feet(Q)	612/396(W/O Pallets/With Pallets)	612/396(W/O Pallets/With Pallets)	364/308(W/O Pallets/With Pallets)	364/308(W/O Pallets/With Pallets)	364/308(W/O Pallets/With Pallets)	
Accessory	Accessory	DC12V Adaptor Remote Control Manual Battery PC D-SUB cable(option)	DC15V Adaptor Remote Control Manual Battery -	Power cord Remote Control Manual Battery PC D-SUB cable(option)	Power cord Remote Control Manual Battery PC D-SUB cable(option)	Power cord Remote Control Manual Battery PC D-SUB cable(option)	

Specifications-LCD...



Section	Contents	DL26-M22P	DL26-M70P	DL32-B22P	DL32-B70P	DL32-C10P
Display	Outline Dimension	626.0(H) mm x 373.0(V) mm	626.0(H) mm x 373.0(V) mm	760.0(H) mm x 450.0(V) mm	760.0(H) mm x 450.0(V) mm	760.0(H) mm x 450.0(V) mm
	Active area	566.4(H) mm x 339.8(V) mm	566.4(H) mm x 339.8(V) mm	697.7(H) mm x 392.3(V) mm	697.7(H) mm x 392.3(V) mm	697.7(H) mm x 392.3(V) mm
	Aspect Ratio	16 : 9	16 : 9	16:9	16:9	16:9
	Pixel Pitch	147.5mm x 421.5mm x RGB	147.5mm x 421.5mm x RGB	170.25um x 510.75um x RGB	170.25um x 510.75um x RGB	170.25um x 510.75um x RGB
	Resolutions	1,366 x RGB x 768	1,366 x RGB x 768	1,366 x RGB x 768	1,366 x RGB x 768	1,366 x RGB x 768
	Viewing Angle	L/R 176, U/D 176	L/R 176, U/D 176	L/R 176, U/D 176	L/R 176, U/D 176	L/R 176, U/D 176
	Colors	16.7M	16.7M	16.7M	16.7M	16.7M
	Luminance	500 cd/m ²	500 cd/m ²	500 cd/m ²	500 cd/m ²	500 cd/m ²
	Contrast Ratio	600 : 1	600 : 1	600 : 1	600 : 1	600 : 1
Response Time	16 ms	16 ms	16 ms	16 ms	16 ms	
System	Tuning	PAL-B/G ,D/K, I SECAM-B/G,D/K,L/L' NTSC AV 3.58/4.43	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC AV 3.58/4.43	PAL-B/G ,D/K, I SECAM-B/G,D/K,L/L' NTSC AV 3.58/4.43	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC AV 3.58/4.43	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC AV 3.58/4.43
	Audio	A2 STEREO NICAM STEREO MTS/SAP(NTSC Area)	A2 STEREO NICAM STEREO MTS/SAP(NTSC Area)	A2 STEREO NICAM STEREO MTS/SAP(NTSC Area)	A2 STEREO NICAM STEREO MTS/SAP(NTSC Area)	A2 STEREO NICAM STEREO MTS/SAP(NTSC Area)
	Speaker	Side 2 Speaker(Built-in)	Side 2 Speaker(Built-in)	Side 2 Speaker(Built-in)	Side 2 Speaker(Built-in)	Side 2 Speaker(Built-in)
	Teletext	252 pages	1000 pages	252 pages	1000 pages	200 Page
	V-Chip/CCD	O (US)	O (US)	O (US)	O (US)	O (US)
	Audio	10W(5W x 2W)max	20W(10W + 10W) / RMS	10W(5W x 2W) / RMS	20W(10W + 10W) / RMS	20W(10W + 10W) / RMS
	Multi Language OSD	ENG/DEUT/FRA/ITA/ESP	ENG/DEUT/FRA/ITA/ESP	ENG/DEUT/FRA/ITA/ESP	ENG/DEUT/FRA/ITA/ESP	ENG/DEUT/FRA/ITA/ESP
Picture	16:9 / 4:3	16:9,4:3,Zoom, Panorama	16:9 / 4:3	16:9,4:3,Zoom, Panorama	ARC(Auto wide/Wide/Panorama/Zoom/4:3/14:9)	
Function	Function	3D NR Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher Picture Tone(Normal/Warm/Cool) Picture (User/Standard/ Movie/Vivid) Sound (User/Standard /Music/Movie/News) Sleep Timer/PIP(Only PC Mode)	4H Comb Filter Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher APC(Standard/Soft/Custom/Strong) ASC(Standard/Music/Movie/Speech /User/Surround Auto Power On,Off/Sleep Timer/On,Off Timer PIP/POP/DW	3D NR Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher Picture Tone(Normal/Warm/Cool) Picture (User/Standard/ Movie/Vivid) Sound (User/Standard /Music/Movie/News) Sleep Timer/PIP(Only PC Mode)	4H Comb Filter Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher APC(Standard/Soft/Custom/Strong) ASC(Standard/Music/Movie/Speech /User/Surround Auto Power On,Off/Sleep Timer/On,Off Timer PIP/POP/DW	- Surround Sleep timer On/Off Timer PSM(Custom/Dynamic/Standard/Movie/Mild) SSM(Custom/Standard/Music/Movie/Speech) Movie/User/Surround Auto Power On/Off PIP / DW (Double Window) Still/move/Swap
	AV input	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack
	PC Video input	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin
	PC Audio Input	Ear Phone Jack	Audio L/R RCA Jack	Ear Phone Jack	Audio L/R RCA Jack	Ear Phone Jack
	DVI Input	DVI (with HDCP)	-	DVI (With HDCP)	-	DVI (With HDCP)
	RS-232	-	O (UP-Grade)	-	O(UP-Grade)	O
	HDMI	-	O	-	O	-
	Speaker	Bulti in Speaker	Bulti in Speaker	Bulti in Speaker	Bulti in Speaker	External Speaker
	Head Phone Output	Head Phone Jack	Ear Phone Jack	Head Phone Jack	Head Phone Jack	Head Phone Jack
Antenna In	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	
Power	Input Voltage	100~240V(50/60Hz)	100~240V(50/60Hz)	100V - 240V (50/60Hz)	100V - 240V (50/60Hz)	100V - 240V (50/60Hz)
	consumption	Approx.120W	Approx.120W	Approx. 150W	Approx. 150W	Approx. 150W
Mechanical Size	Size (W x D x H) mm	650 X 230 x 550(With Stand) 650 x 96 X 505 (w/o stand)	650 X 230 x 550(With Stand) 650 x 96 X 505 (w/o stand)	925 X 263.3 X 545 (With Stand) 925 X 97 X 491.2 (w/o stand)	925 X 263.3 X 545 (With Stand) 925 X 97 X 491.2 (w/o stand)	925 X 263.3 X 545 (With Stand) 925 X 97 X 491.2 (w/o stand)
	Weight (N.Weight/ G.Weight)	19kg/22kg	19kg/22kg	18.7kg / 23kg	18.7kg / 23kg	18.7kg / 23kg
Container	20 Feet	144/120(W/O Pallets/With Pallets)	144/120(W/O Pallets/With Pallets)	108/60(W/O Pallets/With Pallets)	108/60(W/O Pallets/With Pallets)	108/60(W/O Pallets/With Pallets)
	40 Feet	312/264(W/O Pallets/With Pallets)	312/264(W/O Pallets/With Pallets)	228/132(W/O Pallets/With Pallets)	228/132(W/O Pallets/With Pallets)	228/132(W/O Pallets/With Pallets)
	40 Feet(Q)	364/308(W/O Pallets/With Pallets)	364/308(W/O Pallets/With Pallets)	266/154(W/O Pallets/With Pallets)	266/154(W/O Pallets/With Pallets)	266/154(W/O Pallets/With Pallets)
Accessory	Accessory	Power cord Remote Control Manual Battery PC D-SUB cable(option)	Power cord Remote Control Manual Battery PC D-SUB cable(option)	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)

Specifications-LCD...



Section	Contents	DL32-G10P	DL32-G22P	DL32-G70P	DL32-M22P	DL32-M70P	
Display	Outline Dimension	760.0(H) mm x 450.0(V) mm	760.0(H) mm x 450.0(V) mm	760.0(H) mm x 450.0(V) mm	760.0(H) mm x 450.0(V) mm	760.0(H) mm x 450.0(V) mm	
	Active area	697.7(H) mm x 392.3(V) mm	697.7(H) mm x 392.3(V) mm	697.7(H) mm x 392.3(V) mm	697.7(H) mm x 392.3(V) mm	697.7(H) mm x 392.3(V) mm	
	Aspect Ratio	16:9	16:9	16:9	16:9	16:9	
	Pixel Pitch	170.25um x 510.75um x RGB	170.25um x 510.75um x RGB	170.25um x 510.75um x RGB	170.25um x 510.75um x RGB	170.25um x 510.75um x RGB	
	Resolutions	1,366 x RGB x 768	1,366 x RGB x 768	1,366 x RGB x 768	1,366 x RGB x 768	1,366 x RGB x 768	
	Viewing Angle	L/R 176, U/D 176	L/R 176, U/D 176	L/R 176, U/D 176	L/R 176, U/D 176	L/R 176, U/D 176	
	Colors	16.7M	16.7M	16.7M	16.7M	16.7M	
	Luminance	500 cd/m ²	500 cd/m ²	500 cd/m ²	500 cd/m ²	500 cd/m ²	
	Contrast Ratio	600 :1	600 :1	600 :1	600 :1	600 :1	
	Response Time	16 ms	16 ms	16 ms	16 ms	16 ms	
System	Tuning	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC AV 3.58/4.43	PAL-B/G ,D/K, I SECAM-B/G,D/K,L/L' NTSC AV 3.58/4.43	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC AV 3.58/4.43	PAL-B/G ,D/K, I SECAM-B/G,D/K,L/L' NTSC AV 3.58/4.43	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC AV 3.58/4.43	
	Audio	A2 STEREO NICAM STEREO MTS/SAP(NTSC Area)	A2 STEREO NICAM STEREO MTS/SAP(NTSC Area)	A2 STEREO NICAM STEREO MTS/SAP(NTSC Area)	A2 STEREO NICAM STEREO MTS/SAP(NTSC Area)	A2 STEREO NICAM STEREO MTS/SAP(NTSC Area)	
	Speaker	Side 2 Speaker(Built-in)	Side 2 Speaker(Built-in)	Side 2 Speaker(Built-in)	Side 2 Speaker(Built-in)	Side 2 Speaker(Built-in)	
	Teletext	200 Page	252 pages	1000 pages	252 pages	1000 pages	
	V-Chip/CCD	O (US)	O (US)	O (US)	O (US)	O (US)	
	Output	Audio Multi Language OSD Picture	20W(10W + 10W) / RMS ENG/DEUT/FRA/ITA/ESP ARC(Auto wide/Wide/Panorama/Zoom/4:3/14:9)	10W(5W x W2)max ENG/DEUT/FRA/ITA/ESP	20W(10W + 10W) / RMS ENG/DEUT/FRA/ITA/ESP 16:9,4:3,Zoom,Panorama	10W(5W x 2W)max ENG/DEUT/FRA/ITA/ESP 16:9 / 4:3	20W(10W + 10W) / RMS ENG/DEUT/FRA/ITA/ESP 16:9,4:3,Zoom,Panorama
	Function	Function	- Surround Sleep timer On/Off Timer PSM(Custom/Dynamic/Standard/Movie/Mild) SSM(Custom/Standard/Music/Movie/Speech) Movie/User/Surround Auto Power On/Off PIP / DW (Double Window) Still/move/Swap	3D NR Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher Picture Tone(Normal/Warm/Cool) Picture (User/Standard/ Movie/Vivid) Sound (User/Standard /Music/Movie/News) Sleep Timer/PIP(Only PC Mode)	4H Comb Filter Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher APC(Standard/Soft/Custom/Strong) ASC(Standard/Music/Movie/Speech) /User/Surround Auto Power On,Off/Sleep Timer/On,Off Timer PIP/POP/DW	3D NR Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher Picture Tone(Normal/Warm/Cool) Picture (User/Standard/ Movie/Vivid) Sound (User/Standard /Music/Movie/News) Sleep Timer/PIP(Only PC Mode)	4H Comb Filter Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher APC(Standard/Soft/Custom/Strong) ASC(Standard/Music/Movie/Speech) /User/Surround Auto Power On,Off/Sleep Timer/On,Off Timer PIP/POP/DW
In/Out Terminal		AV input	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack
		PC Video input	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin
		PC Audio Input	Ear Phone Jack	Ear Phone Jack	Audio L/R RCA Jack	Ear Phone Jack	Audio L/R RCA Jack
		DVI Input	DVI (With HDCP)	DVI (With HDCP)	-	DVI (With HDCP)	-
		RS-232	O	-	O (UP-Grade)	-	O (UP-Grade)
		HDMI	-	-	O	-	O
		Speaker	Bulti in Speaker	Bulti in Speaker	Bulti in Speaker	Bulti in Speaker	Bulti in Speaker
		Head Phone Output	Head Phone Jack	Head Phone Jack	Head Phone Jack	Head Phone Jack	Head Phone Jack
		Antenna In	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack
	Power	Input Voltage consumption	100V - 240V (50/60Hz) Approx. 150W	100V - 240V (50/60Hz) Approx. 150W	100V - 240V (50/60Hz) Approx. 150W	100V - 240V (50/60Hz) Approx. 150W	100V - 240V (50/60Hz) Approx. 150W
Mechanical Size	Size (W x D x H) mm	950.6 X 230 X 561.8 (With Stand) 950.6 X 230 X512.6 (w/o stand)	950.6 X 230 X 561.8 (With Stand) 950.6 X 230 X512.6 (w/o stand)	950.6 X 230 X 561.8 (With Stand) 950.6 X 230 X512.6 (w/o stand)	804 X 230 X 623 (With Stand) 806 x 96.5 X 572 (w/o stand)	804 X 230 X 623 (With Stand) 806 x 96.5 X 572 (w/o stand)	
	Weight (N.Weight/ G.Weight)	18.7kg / 23kg	18.7kg / 23kg	18.7kg / 23kg	18.7kg / 23kg	18.7kg / 23kg	
Container	20 Feet	126/70(W/O Pallets/With Pallets)	126/70(W/O Pallets/With Pallets)	126/70(W/O Pallets/With Pallets)	126/70(W/O Pallets/With Pallets)	126/70(W/O Pallets/With Pallets)	
	40 Feet	266/154(W/O Pallets/With Pallets)	266/154(W/O Pallets/With Pallets)	266/154(W/O Pallets/With Pallets)	266/154(W/O Pallets/With Pallets)	266/154(W/O Pallets/With Pallets)	
	40 Feet(Q)	304/176(W/O Pallets/With Pallets)	304/176(W/O Pallets/With Pallets)	304/176(W/O Pallets/With Pallets)	304/176(W/O Pallets/With Pallets)	304/176(W/O Pallets/With Pallets)	
Accessory	Accessory	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)	

Specifications-LCD...



Section	Contents	DL37-C00P	DL37-G00P	DL37-G70P	DL37-G80P	DL37-K00P	
Display	Outline Dimension	877.0(H) mm X 516.8(V) mm	877.0(H) mm X 516.8(V) mm	877.0(H) mm X 516.8(V) mm	877.0(H) mm X 516.8(V) mm	877.0(H) mm X 516.8(V) mm	
	Active area	819.6(H) mm X 460.8(V) mm	819.6(H) mm X 460.8(V) mm	819.6(H) mm X 460.8(V) mm	819.6(H) mm X 460.8(V) mm	819.6(H) mm X 460.8(V) mm	
	Aspect Ratio	16:9	16:9	16:9	16:9	16:9	
	Pixel Pitch	0.200mm X 0.600mm X RGB	0.200mm X 0.600mm X RGB	0.200mm X 0.600mm X RGB	0.200mm X 0.600mm X RGB	0.200mm X 0.600mm X RGB	
	Resolutions	1,366 X RGB X 768	1,366 X RGB X 768	1,366 X RGB X 768	1,366 X RGB X 768	1,366 X RGB X 768	
	Viewing Angle	R/L 176, U/D 176 (Angle free)	R/L 176, U/D 176 (Angle free)	R/L 176, U/D 176 (Angle free)	R/L 176, U/D 176 (Angle free)	R/L 176, U/D 176 (Angle free)	
	Colors	16.7M	16.7M	16.7M	16.7M	16.7M	
	Luminance	500 cd/m ²	500 cd/m ²	500 cd/m ²	500 cd/m ²	500 cd/m ²	
	Contrast Ratio	600 :1	600 :1	600 :1	600 :1	600 :1	
Response Time	16 ms	16 ms	16 ms	16 ms	16 ms		
System	Tuning	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC- M	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC- M	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC- M	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC- M	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC- M	
	Audio	A2 STEREO NICAM STEREO	A2 STEREO NICAM STEREO	A2 STEREO NICAM STEREO	A2 STEREO NICAM STEREO	A2 STEREO NICAM STEREO	
	Speaker	Side 2 Speaker	Side 2 Speaker	Side 2 Speaker	Side 2 Speaker	Side 2 Speaker	
	Teletext	128 Page	128 Page	1000 Page	1000 Page	128 Page	
	V-Chip/CCD	O (US)	O (US)	O (US)	O (US)	O (US)	
	Output	Audio Multi Language OSD Picture	20W(10W + 10W) / RMS ENG/DEUT/FRA/ITA/ESP 16:9,4:3,Zoom, Panorama	20W(10W + 10W) / RMS ENG/DEUT/FRA/ITA/ESP 16:9,4:3,Zoom, Panorama	20W(10W + 10W) / RMS ENG/DEUT/FRA/ITA/ESP 16:9,4:3,Zoom, Panorama	20W(10W + 10W) / RMS ENG/DEUT/FRA/ITA/ESP/DEUT/RUS/TUR 16:9,4:3,Zoom	20W(10W + 10W) / RMS ENG/DEUT/FRA/ITA/ESP 16:9,4:3,Zoom, Panorama
Function	Function	3D Digital Comb Filter(NTSC Only) Sleep timer On/Off Timer Auto Power On/Off APC(Standard/Soft/Custom/Strong) ASC(Standard/Music/Speech/ Movie/User/Surround) Auto Power On/Off PIP / DW (Double Window) Still/move/Swap	3D Digital Comb Filter(NTSC Only) Sleep timer On/Off Timer Auto Power On/Off APC(Standard/Soft/Custom/Strong) ASC(Standard/Music/Speech/ Movie/User/Surround) Auto Power On/Off PIP / DW (Double Window) Still/move/Swap	4H Comb Filter Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher APC(Standard/Soft/Custom/Strong) ASC(Standard/Music/Movie/Speech /User/Surround) Auto Power On,Off/Sleep Timer/On,Off Timer PIP/POP/DW	3D Digital Comb Filter Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher APC(Standard/Dynamic/Mild/User) ASC(Standard/Music/Movie/Speech /User) Auto Power On,Off/Sleep Timer/On,Off Timer PIP/POP/DW	3D Digital Comb Filter(NTSC Only) Sleep timer On/Off Timer Auto Power On/Off APC(Standard/Soft/Custom/Strong) ASC(Standard/Music/Speech/ Movie/User/Surround) Auto Power On/Off PIP / DW (Double Window) Still/move/Swap	
	In/Out Terminal	AV input	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack	S - VHS (S-VIDEO) AV1 (Full Scart or RCA) AV2 (Half Scart or RCA) Component Video (RCA Jack) Audio L/R RCA Jack
		PC Video input	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin
		PC Audio Input	Ear Phone Jack	Ear Phone Jack	Audio L/R RCA Jack	Ear Phone Jack	Ear Phone Jack
		DVI Input	DVI (With HDCP)	DVI (With HDCP)	-	O	DVI (With HDCP)
		RS-232	-	-	O (UP-Grade)	O (UP-Grade)	-
		HDMI	-	-	O	O	-
		Speaker	External Speaker	Bulti in Speaker	Bulti in Speaker	Bulti in Speaker	Bulti in Speaker
Head Phone Output		-	-	Head Phone Jack	Audio Out(RCA Jack)	-	
Antenna In		PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	
Power		Input Voltage consumption	100V - 240V (50/60Hz) Approx. 200W	100V - 240V (50/60Hz) Approx. 200W	100V - 240V (50/60Hz) Approx. 200W	100V - 240V (50/60Hz) Approx. 200W	100V - 240V (50/60Hz) Approx. 200W
Mechanical Size	Size (W x D x H) mm	921 X 263.3 X 623(With Stand,With Speaker) 921 X 105 X 567(w/o stand,w/o Speaker)	1,076 X 240 X 632 (With Stand) 1,076 X 114 X 564(w/o stand)	1,076 X 240 X 632 (With Stand) 1,076 X 114 X 564(w/o stand)	1,076 X 240 X 632 (With Stand) 1,076 X 114 X 564(w/o stand)	1,076 X 240 X 638 (With Stand) 1,076 X 114 X 569.5(w/o stand)	
	Weight (N.Weight/ G.Weight)	31kg / 37kg	28kg / 33.3kg	28kg / 33.3kg	28kg / 33.3kg	28kg / 33.3kg	
Container	20 Feet	65/63(W/O Pallets/With Pallets)	65/63(W/O Pallets/With Pallets)	65/63(W/O Pallets/With Pallets)	65/63(W/O Pallets/With Pallets)	65/63(W/O Pallets/With Pallets)	
	40 Feet	130/126(W/O Pallets/With Pallets)	130/126(W/O Pallets/With Pallets)	130/126(W/O Pallets/With Pallets)	130/126(W/O Pallets/With Pallets)	130/126(W/O Pallets/With Pallets)	
	40 Feet(Q)	130/126(W/O Pallets/With Pallets)	130/126(W/O Pallets/With Pallets)	130/126(W/O Pallets/With Pallets)	130/126(W/O Pallets/With Pallets)	130/126(W/O Pallets/With Pallets)	
Accessory	Accessory	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)	

Specifications-LCD...



Section	Contents	DL37-K70P	DL37-M70P	DL42-C70P	DL42-G70P	DL42-G80P
Display	Outline Dimension	877.0(H) mm X 516.8(V) mm	877.0(H) mm X 516.8(V) mm	1006(H) mm X 610(V) mm	1006(H) mm X 610(V) mm	1006(H) mm X 610(V) mm
	Active area	819.6(H) mm X 460.8(V) mm	819.6(H) mm X 460.8(V) mm	930.25(H) mm X 523.01(V) mm	930.25(H) mm X 523.01(V) mm	930.25(H) mm X 523.01(V) mm
	Aspect Ratio	16:9	16:9	16:9	16:9	16:9
	Pixel Pitch	0.200mm X 0.600mm X RGB	0.200mm X 0.600mm X RGB	0.227mm X 0.681mm X RGB	0.227mm X 0.681mm X RGB	0.227mm X 0.681mm X RGB
	Resolutions	1,366 X RGB X 768	1,366 X RGB X 768	1,366 X RGB X 768	1,366 X RGB X 768	1,366 X RGB X 768
	Viewing Angle	R/L 176, U/D 176 (Angle free)	R/L 176, U/D 176 (Angle free)	L/R 176, U/D 176 (Angle Free)	L/R 176, U/D 176 (Angle Free)	L/R 176, U/D 176 (Angle Free)
	Colors	16.7M	16.7M	16.7M	16.7M	16.7M
	Luminance	500 cd/m ²	500 cd/m ²	500 cd/m ²	500 cd/m ²	500 cd/m ²
	Contrast Ratio	600 :1	600 :1	500 :1	500 :1	500 :1
	Response Time	16 ms	16 ms	16 ms	16 ms	16 ms
System	Tuning	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC- M	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC- M	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC AV 3.58/4.43	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC AV 3.58/4.43	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC- M
	Audio	A2 STEREO NICAM STEREO	A2 STEREO NICAM STEREO	A2 STEREO NICAM STEREO	A2 STEREO NICAM STEREO	A2 STEREO NICAM STEREO
	Speaker	Side 2 Speaker	Side 2 Speaker	Side 2 Speaker	Side 2 Speaker	Side 2 Speaker
	Teletext	1000 Page	1000 Page	1000 Page	1000 Page	1000 Page
	V-Chip/CCD	O (US)	O (US)	O (US)	O (US)	O (US)
	Output	Audio Multi Language OSD Picture	20W(10W + 10W) / RMS ENG/DEUT/FRA/ITA/ESP 16:9,4:3,Zoom, Panorama	20W(10W + 10W) / RMS ENG/DEUT/FRA/ITA/ESP 16:9,4:3,Zoom, Panorama	20W(10W + 10W) / RMS ENG/DEUT/FRA/ITA/ESP 16:9,4:3,Zoom, Panorama	20W(10W + 10W) / RMS ENG/DEUT/FRA/ITA/ESP 16:9,4:3,Zoom, Panorama
Function	Function	4H Comb Filter Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher APC(Standard/Soft/Custom/Strong) ASC(Standard/Music/Movie/Speech /User/Surround Auto Power On,Off/Sleep Timer/On,Off Timer PIP/POP/DW	4H Comb Filter Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher APC(Standard/Soft/Custom/Strong) ASC(Standard/Music/Movie/Speech /User/Surround Auto Power On,Off/Sleep Timer/On,Off Timer PIP/POP/DW	4H Comb Filter Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher APC(Standard/Soft/Custom/Strong) ASC(Standard/Music/Movie/Speech /User/Surround Auto Power On,Off/Sleep Timer/On,Off Timer PIP/POP/DW	4H Comb Filter Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher APC(Standard/Soft/Custom/Strong) ASC(Standard/Music/Movie/Speech /User/Surround Auto Power On,Off/Sleep Timer/On,Off Timer PIP/POP/DW	3D Digital Comb Filter Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCTI Film- Mode/Black Stretcher APC(Standard/Dynamic/Mild/User) ASC(Standard/Music/Movie/Speech /User) Auto Power On,Off/Sleep Timer/On,Off Timer PIP/POP/DW
	AV input	S - VHS (S-VIDEO)	S - VHS (S-VIDEO)	S - VHS (S-VIDEO)	S - VHS (S-VIDEO)	S - VHS (S-VIDEO)
		AV1 (Full Scart or RCA)	AV1 (Full Scart or RCA)	AV1 (Full Scart or RCA)	AV1 (Full Scart or RCA)	AV1 (Full Scart or RCA)
		AV2 (Half Scart or RCA)	AV2 (Half Scart or RCA)	AV2 (Half Scart or RCA)	AV2 (Half Scart or RCA)	AV2 (Half Scart or RCA)
		Component Video (RCA Jack)	Component Video (RCA Jack)	Component Video (RCA Jack)	Component Video (RCA Jack)	Component Video (RCA Jack)
	Audio L/R RCA Jack	Audio L/R RCA Jack	Audio L/R RCA Jack	Audio L/R RCA Jack	Audio L/R RCA Jack	
	PC Video input	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin
	PC Audio Input	Audio L/R RCA Jack	Audio L/R RCA Jack	Audio L/R RCA Jack	Audio L/R RCA Jack	Ear Phone Jack
DVI Input	-	-	-	-	O	
RS-232	O (UP-Grade)	O (UP-Grade)	O (UP-Grade)	O (UP-Grade)	O (UP-Grade)	
HDMI	O	O	O	O	O	
Speaker	Bulti in Speaker	Bulti in Speaker	External Speaker	Bulti in Speaker	Bulti in Speaker	
Head Phone Output	Head Phone Jack	Head Phone Jack	Head Phone Jack	Ear Phone Jack	Audio Out(RCA Jack)	
Antenna In	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	PAL;Din-Jack/NTSC: F-Jack	
Power	Input Voltage	100V - 240V (50/60Hz)	100V - 240V (50/60Hz)	100V - 240V (50/60Hz)	100V - 240V (50/60Hz)	100V - 240V (50/60Hz)
	consumption	Approx. 200W	Approx. 200W	Approx. 300W	Approx. 300W	Approx. 300W
Mechanical Size	Size (W x D x H) mm	1,076 X 240 X 638 (With Stand) 1,076 X 114 X 569.5(w/o stand)	923 X 240 X 714 (With Stand) 923 X 115 X 646(w/o stand)	1,212 X 240 X 721(With Stand) 1,212 X 118 X 653.5 (w/o stand)	1,212 X 240 X 721(With Stand) 1,212 X 118 X 653.5 (w/o stand)	1,212 X 240 X 721(With Stand) 1,212 X 118 X 653.5 (w/o stand)
	Weight (N.Weight/ G.Weight)	28kg / 33.3kg	30kg / 35kg	34.2kg / 40.5kg	34.2kg / 40.5kg	34.2kg / 40.5kg
Container	20 Feet	65/63(W/O Pallets/With Pallets)	65/63(W/O Pallets/With Pallets)	45/45(W/O Pallets/With Pallets)	48/48(W/O Pallets/With Pallets)	48/48(W/O Pallets/With Pallets)
	40 Feet	130/126(W/O Pallets/With Pallets)	130/126(W/O Pallets/With Pallets)	90/90(W/O Pallets/With Pallets)	96/96(W/O Pallets/With Pallets)	96/96(W/O Pallets/With Pallets)
	40 Feet(Q)	130/126(W/O Pallets/With Pallets)	130/126(W/O Pallets/With Pallets)	-	96/96(W/O Pallets/With Pallets)	96/96(W/O Pallets/With Pallets)
Accessory	Accessory	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)	User Manual Remote Control Battery Power Cord PC D-SUB cable(option)

Specifications-PDP...



Section	Contents	DP42-D30PH	DP42-D30P(SD)	DP42-D50P(SD)	DP42-JA0P(SD)	DP42-J30P	DP42-J30P(SD)	DP42-D30PH
Display	Outline Dimension	1005(H) mm X 597(V) mm	1005(H) mm X 597(V) mm	1000(H) mm X 588(V) mm	1000(H) mm X 588(V) mm	1005(H) mm X 597(V) mm	1005(H) mm X 597(V) mm	1190(H) mm X 700(H) mm
	Active area	920.1(H) mm X 518.4(V) mm	920.1(H) mm X 518.4(V) mm	932.94(H) mm X 532.80(V) mm	932.94(H) mm X 532.80(V) mm	920.1(H) mm X 518.4(V) mm	920.1(H) mm X 518.4(V) mm	1106.5(H) mm X 622.1(H) mm
	Aspect Ratio	16:9	16:9	16:9	16:9	16:9	16:9	16 : 9
	Pixel Pitch	900um X 676um	1080um X 1080um	1.095mm X 1.110mm	1.095mm X 1.110mm	900um X 676um	1080um X 1080um	810S-(H) X 810S-(V)
	Resolutions	1024 X 768 X RGB(XGA)	852 X 480 X RGB(WVGA)	852 X 480 X RGB(WVGA)	852 X 480 X RGB(WVGA)	1024 X 768 X RGB(XGA)	852 X 480 X RGB(WVGA)	1,366 X 768 X RGB(WVGA)
	Brightness	1000 cd/m ²	1500 cd/m ²	1500 cd/m ²	1500 cd/m ²	1000 cd/m ²	1500 cd/m ²	1,000cd/m ²
	Contrast Ratio	5000 : 1	10,000 : 1	10,000 : 1	10,000 : 1	5000 : 1	10,000 : 1	8,000:1
	Life Time	More than 60,000Hours	More than 60,000Hours	More than 60,000Hours	More than 60,000Hours	More than 60,000Hours	More than 60,000Hours	More than 60,000Hours
System	System	PAL- B/G, D/K, I	PAL- B/G, D/K, I	PAL- B/G, D/K, I	PAL- B/G, D/K, I	PAL- B/G, D/K, I	PAL- B/G, D/K, I	PAL- B/G, D/K, I
	Tuner	SECAM - B/G,D/K, L/L'	SECAM - B/G,D/K, L/L'	SECAM - B/G,D/K, L/L'	SECAM - B/G,D/K, L/L'	SECAM - B/G,D/K, L/L'	SECAM - B/G,D/K, L/L'	SECAM - B/G,D/K, L/L'
	Channel	VHF/UHF/CATV/Hyper	VHF/UHF/CATV/Hyper	VHF/UHF/CATV/Hyper	VHF/UHF/CATV/Hyper	VHF/UHF/CATV/Hyper	VHF/UHF/CATV/Hyper	VHF/UHF/CATV/Hyper
Video	Picture Improvement	3D Digital Comb Filter(NTSC Only)	3D Digital Comb Filter(NTSC Only)	3D Digital Comb Filter(NTSC Only)	3D NR	3D Digital Comb Filter(NTSC Only)	3D Digital Comb Filter(NTSC Only)	3D Digital Comb Filter(NTSC Only)
		Motion Adaptive De-interface	Motion Adaptive De-interface	Motion Adaptive De-interface	Motion Adaptive De-interface	Motion Adaptive De-interface	Motion Adaptive De-interface	Motion Adaptive De-interface
		Motion Adaptive Noise Reduction	Motion Adaptive Noise Reduction	Motion Adaptive Noise Reduction	Motion Adaptive Noise Reduction	Motion Adaptive Noise Reduction	Motion Adaptive Noise Reduction	Motion Adaptive Noise Reduction
		Edge Smooth	Edge Smooth	Edge Smooth	Edge Smooth	Edge Smooth	Edge Smooth	Edge Smooth
		DLTI/DCTI	DLTI/DCTI	DLTI/DCTI	DLTI/DCTI	DLTI/DCTI	DLTI/DCTI	DLTI/DCTI
		Black Stretcher	Black Stretcher	Black Stretcher	Black Stretcher	Black Stretcher	Black Stretcher	Black Stretcher
	PIP,POP,D/W	PIP,D/W(Double Window)	PIP,D/W(Double Window)	PIP,D/W(Double Window)	PIP(Only PC Mode)	PIP,D/W(Double Window)	PIP,D/W(Double Window)	PIP,D/W(Double Window)
	Picture User Control	Con/Bri/Tint/Color/Sharpness	Con/Bri/Tint/Color/Sharpness	Con/Bri/Tint/Color/Sharpness	Con/Bri/Tint/Color/Sharpness	Con/Bri/Tint/Color/Sharpness	Con/Bri/Tint/Color/Sharpness	Con/Bri/Tint/Color/Sharpness
Picture Mode	Strong, Standard,Soft,Custom	Strong, Standard,Soft,Custom	Strong, Standard,Soft,Custom	Picture (User/Standard/ Movie/Vivid)	Strong, Standard,Soft,Custom	Strong, Standard,Soft,Custom	Strong, Standard,Soft,Custom	
Audio	Max Out-Put	20W(10W + 10W) / RMS	20W(10W + 10W) / RMS	20W(10W + 10W) / RMS	20W(10W + 10W) / RMS	20W(10W + 10W) / RMS	20W(10W + 10W) / RMS	20W(10W + 10W)/RMS
	Stereo	A2 + NICAM STEREO	A2 + NICAM STEREO	A2 + NICAM STEREO	A2 + NICAM STEREO	A2 + NICAM STEREO	A2 + NICAM STEREO	A2 + NICAM STEREO
	Sound Mode	Surround,Standard,Music, Speech, Movie, User(6 Mode)	Surround,Standard,Music, Speech, Movie, User(6 Mode)	Surround,Standard,Music, Speech, Movie, User(6 Mode)	Sound (User/Standard /Music/Movie/News)	Surround,Standard,Music, Speech, Movie, User(6 Mode)	Surround,Standard,Music, Speech, Movie, User(6 Mode)	Surround,Standard,Music, Speech, Movie, User(6 Mode)
	Catpion/Teletext	Teletext 128 Pages	Teletext 128 Pages	Teletext 128 Pages	Teletext 252 Pages	Teletext 128 Pages	Teletext 128 Pages	Teletext 128 Pages
Features	OSD(Menu System)	ENG/DEUT/FRA/ITA/ESP	ENG/DEUT/FRA/ITA/ESP	ENG/DEUT/FRA/ITA/ESP	ENG/DEUT/FRA/ITA/ESP	ENG/DEUT/FRA/ITA/ESP	ENG/DEUT/FRA/ITA/ESP	ENG/DEUT/FRA/ITA/ESP
	Clock	Simple ICON Type	Simple ICON Type	Simple ICON Type	Simple ICON Type	Simple ICON Type	Simple ICON Type	Simple ICON Type
		Sleep Timer	Sleep Timer	Sleep Timer	Sleep Timer	Sleep Timer	Sleep Timer	Sleep Timer
		ON/OFF Timer	ON/OFF Timer	ON/OFF Timer	ON/OFF Timer	ON/OFF Timer	ON/OFF Timer	ON/OFF Timer
		Auto Power On/Off	Auto Power On/Off	Auto Power On/Off	Auto Power On/Off	Auto Power On/Off	Auto Power On/Off	Auto Power On/Off
In/Out Terminal	AV input	S-Video	S-Video	S-Video	S-Video	S-Video	S-Video	S-Video
		Full/Half Scart	Full/Half Scart	Full/Half Scart	Full/Half Scart	Full/Half Scart	Full/Half Scart	Composite(RCA Jack)
		Audio L/R RCA Jack	Audio L/R RCA Jack	Audio L/R RCA Jack	Audio L/R RCA Jack	Audio L/R RCA Jack	Audio L/R RCA Jack	Audio L/R RCA Jack
		Component Video (RCA Jack)	Component Video (RCA Jack)	Component Video (RCA Jack)	Component Video (RCA Jack)	Component Video (RCA Jack)	Component Video (RCA Jack)	Component Video (RCA Jack)
		DVI (With HDCP)	DVI (With HDCP)	DVI (With HDCP)	DVI (With HDCP)	DVI (With HDCP)	DVI (With HDCP)	DVI (With HDCP)
	PC Video input	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin	D-Sub Jack / 15 Pin
	PC Audio Input	Ear Phone Jack	Ear Phone Jack	Ear Phone Jack	Ear Phone Jack	Ear Phone Jack	Ear Phone Jack	Ear Phone Jack
	RS-232	-	-	-	-	-	-	-
	HDMI	-	-	-	-	-	-	-
	Speaker	External Speaker	External Speaker	External Speaker	External Speaker	External Speaker	External Speaker	External Speaker
Head Phone Output	-	-	-	0	-	-	-	
Antenna In	75 Ohm DIN Jack	75 Ohm DIN Jack	75 Ohm DIN Jack	75 Ohm DIN Jack	75 Ohm DIN Jack	75 Ohm DIN Jack	75 Ohm DIN Jack	
Power	Input Voltage	AC100 ~ 240V(50/60Hz)	AC100 ~ 240V(50/60Hz)	AC100 ~ 240V(50/60Hz)	AC100 ~ 240V(50/60Hz)	AC100 ~ 240V(50/60Hz)	AC100 ~ 240V(50/60Hz)	AC100 ~ 240V(50/60Hz)
	consumption	Approx 320W	Approx 320W	Approx 320W	Approx 320W	Approx 320W	Approx 320W	Approx 460W
Mechanical Size	Size (W x D x H) mm	1,050 X 300 X 697(With Stand)	1,050 X 300 X 697(With Stand)	1,050 X 300 X 697(With Stand)	1,033 X 310 X 702(With Stand)	1,033 X 310 X 702(With Stand)	1,033 X 310 X 702(With Stand)	1,230 X 240 X 812(With Stand)
	Weight(Kg)	35Kg(Net)	35Kg(Net)	35Kg(Net)	35Kg(Net)	35Kg(Net)	35Kg(Net)	50Kg(Net)
Container	20 Feet	48 (W/O Pallets)	48 (W/O Pallets)	48 (W/O Pallets)	48 (W/O Pallets)	48 (W/O Pallets)	48 (W/O Pallets)	48 (W/O Pallets)
	40 Feet	108 (W/O Pallets)	108 (W/O Pallets)	108 (W/O Pallets)	108 (W/O Pallets)	108 (W/O Pallets)	108 (W/O Pallets)	96 (W/O Pallets)
Accessory	Accessory	User Manual	User Manual	User Manual	User Manual	User Manual	User Manual	User Manual
		Remote Control	Remote Control	Remote Control	Remote Control	Remote Control	Remote Control	Remote Control
		Battery	Battery	Battery	Battery	Battery	Battery	Battery
		Power Cord	Power Cord	Power Cord	Power Cord	Power Cord	Power Cord	Power Cord
		PC D-SUB cable(option)	PC D-SUB cable(option)	PC D-SUB cable(option)	PC Serial Cable (Option)	PC Serial Cable (Option)	PC Serial Cable (Option)	PC D-SUB cable(option)
		PC D-SUB cable(option)	PC D-SUB cable(option)	PC D-SUB cable(option)	PC Serial Cable (Option)	PC Serial Cable (Option)	PC Serial Cable (Option)	PC D-SUB cable(option)

DECKtron

<http://www.decktron.com>

Seoul Office :

909-3, Handok Bldg.,4F., Dogok-Dong,
Kangnam-Gu, Seoul, Korea, 135-859
Tel: +82-2-555-4755
Fax: +82-2-555-4757
E-mail: info@decktron.com

Head Office & Factory :

Block # 102-18, Ochang Scientific Industrial
Complex, 643-2, Kakri, Ochang-myun,
Cheongwon-kun, Chungbuk, S.Korea. 363-883
Tel : 82 - 43 - 219 - 9600
Fax : 82 - 43 - 219 - 9696